

Galvanised Commercial Wire Rope Grips (Robur Pattern)

Commercial 'Robur' Grips

Rope Dia mm	3	5	6	8	10	11	13	14	16	20	22	26	30	34	40
A mm	4	5	6	6	8	8	10	10	10	12	12	14	14	16	16
L mm	12	13	15	19	22	22	33	33	33	44	44	50	50	55	60
H mm	17	24	27	31	37	41	44	47	51	62	65	72	78	88	98
I mm	9	12	15	17	20	22	25	27	29	35	39	42	48	54	60
E mm	20	24	28	34	42	44	55	57	63	77	85	95	110	120	140
R mm	7	9	10	11	14	15	17	18	20	22	25	27	33	37	40
S mm	10	15	16	19	22	24	26	27	28	33	35	40	43	48	54
Weight Kgs/100	0.7	1.8	2.5	3.2	6.5	8	12	14	17.5	28	32	45	61	87	113

Galvanised Drop Forged Wire Rope Grips meet the performance requirements of US Fed. Spec. FF-C-450 & EN 13411 Pt5 Type B

U.S. Fed Spec Wire
Rope Grips

Rope Dia inches	1/4	5/16	3/8	1/2	5/8	3/4	7/8	1	1 1/8	1 1/4	1 3/8	1 1/2	1 3/4	2	2 1/4	2 1/2	2 3/4	3
A mm	8	10	11	13	16	14	19	19	19	22	22	22	29	32	32	32	32	38
B mm	34	45	49	61	74	86	98	108	117	130	140	147	175	195	208	227	243	271
C mm	19	22	26	30	33	38	45	48	51	59	60	66	78	86	98	105	112	121
D mm	13	19	19	26	32	37	40	46	51	54	59	60	74	78	81	87	91	104
F mm	37	43	49	58	64	72	80	88	91	105	108	112	134	152	162	168	174	194
H mm	30	33	42	48	52	57	62	67	72	79	79	86	97	113	116	119	127	135
L mm	17	18	25	27	33	37	40	44	48	56	58	64	78	87	100	113	124	136
Weight Kgs/100	8	14	19	34	45	68	108	113	140	207	234	266	441	603	707	806	1,000	1,440